

TECHNICAL DATA

	The MLQ	The MLQY
Calibre22 l. r.	.22 short
Number of grooves	6	6
Right-hand twist	400 mm per turn	400 mm per turn
Barrel length with muzzle brake, mm . .	186	186
Barrel length without muzzle brake, mm .	160	160
Sight radius, mm	190	190
Overall length with muzzle brake, mm .	300	300
Overall height with palm rest, mm . . .	146	140
Width, mm	50	50
Distance between foresight and trigger guard (in accordance with the requirements of the International Shooting Union), mm	40	40
Capacity of magazine	6	6
Weight of magazine full, g	102	77
Weight of magazine empty, g	85	56
Total weight, with full magazine and muzzle brake, kg	not over 1.2	not over 1.2
Barrel weights (two), g	50;100	50;100
Trigger pull, kg	0.5-1.0	0.5-1.0
Foresight, changeable, micrometer click-adjustment		
Rear sight, changeable, micrometer click-adjustment		

PISTOL OPERATION

After the shot has been fired the slide travels backward causing the hammer to turn on its pin and go down. The extractor ejects the fired case from the chamber, and the case running against the ejector bracket is forced up to the right. The hammer cocking cam engages behind the sear's sharp edge and is retained in the cocked position. The mainspring is compressed. The slide cotter retracts the retaining block thus compressing the recoil spring. As the slide travels rearward the magazine follower presses the cartridges upward. The next cartridge going up stops at slide level. With the slide travelling forward the feed rib forces the upper cartridge from the magazine directing it to the chamber. The extractor hook engages behind the cartridge rim. Having reached its extreme front position the slide stops and locks

the barrel. The locking of the barrel is ensured by the action of the recoil spring and the inertia of the slide weight.

The cycle will be repeated every time the trigger is pressed until the magazine is empty. With the hammer released, the trigger retracts the trigger bar. It presses the sear side lug (pin) disengaging the sear from the hammer cocking cam. The hammer disengaged from the sear turns on its pin under the action of the mainspring and vigorously strikes against the firing pin. Upon the impact the firing pin with the striker briskly slides forward, the striker comes out of the slide body hole and thrusts against the case rim. Thus the shot is fired.

The left-hand side of the MLQ pistol carries the safety lug. With the lug suppressed into its first fixed position the hammer is set at safety. In this position the shot cannot be fired. As the safety lever is forced all the way down and the slide all the way to the rear the latter engages with the safety lug. Disengagement of the slide is effected by turning the safety lug to its uppermost position.

Adjustment of the sights of both pistols (the foresight in elevation and the rear sight in windage) is done by click-adjusting screws. One click is equal to 1/4 revolution of the adjusting screw which corresponds to the rear sight travelling 0.088 mm horizontally and the foresight 0.088 mm vertically.

PISTOL PARTS

Nos.	Description	Parts number		
		MLQ MLQY	MLQ	MLQY
1	Barrel		1-1	1-1
2	Foresight housing	1-3		
3	Barrel pin	1-4		
4	Side plate	1-6		
5	Side plate screw	1-7		
6	Receiver		1-8	1-8
7	Rear sight bridge	1-9		
8	Rear sight bridge pin	1-10		
9	Rear sight adjustment retaining screw	1-12		
10	Rear sight adjustment spring	1-13		

Nos.	Description	Parts number		
		МЦ МЦУ	МЦ	МЦУ
11	Rear sight blade	1-14		
12	Rear sight adjustment plunger	1-15		
13	Plunger spring	1-16		
14	Slide	-	2-1	2-1
15	Firing pin	2-2		
16	Firing pin spring	2-3		
17	Firing pin retaining pin			
	Magazine catch pin	2-4		
18	Extractor	2-5		
19	Extractor plunger	2-6		
20	Extractor spring	2-7		
21	Slide retaining block	3-1		
22	Recoil spring	3-2		
23	Recoil spring guide	3-3		
24	Slide cotter release knob	3-4		
25	Slide cotter release knob pin	3-5		
26	Hammer strut pin	3-24		
27	Trigger	4-1		
28	Trigger bar	4-2		
29	Trigger bar pin	4-3		
30	Trigger pin	4-43		
31	Hammer	5-1		
32	Hammer strut	5-2		
33	Safety lever		6-1	
34	Magazine catch	1		
35	Magazine catch spring	2		
36	Trigger spring	3		
37	Trigger bar spring	4		
38	Ejector bracket	5		
39	Mainspring	6		
40	Hammer pin	7		
41	Sear	8		
42	Sear pin	9		
43	Sear spring	10		
44	Slide cotter	11		
45	Foresight	12		
46	Foresight adjusting ring	13		

Nos.	Description	Parts number		
		МЦ МЦУ	МЦ	МЦУ
47	Foresight locating screw	14		
48	Foresight screw pin	15		
49	Foresight adjustment plunger	16		
50	Foresight retaining pin	17		
51	Stock screw	18		
52	Foresight clamping screw	19		
53	Trigger stop screw	20		
54	Stock screw	-	-	21
55	Muzzle brake	23		
56	Magazine assembly	-	c6-10	c6-7
57	Left stock	-	c6-8	c6-8
58	Right stock	-	c6-9	c6-9
59	Windage adjustment screw	c6 1-3		
60	Rear stock screw	-	-	22

V/O "Raznoexport" exports hunting and sporting fire-arms and ammunition made in the USSR.